

PBS EXP 13 - PM Semi with 2 or more axle groups L2

Approval under section 9(1)(b)(i) of the Heavy Vehicle (General) National Regulation – Noncompliance

Approval under section 9(1)(b)(i) of the Heavy Vehicle (General) National Regulation – Noncompliance	
The type of heavy vehicle:	PM Semi with 2 or more axle groups (Level 2)
The standard/s under the Standards and Vehicle Assessment Rules that a vehicle built to the design may not comply with:	Maximum of Difference (C8b) Standard: 400mm This vehicle design: 500 mm (exceedance of 100mm)
Reasons why the non-compliance will not pose any additional risk to safety or infrastructure if the particular conditions are imposed and complied with.	<p>The Regulator undertook a risk assessment before determining its support for the design. The Regulator concluded that although a heavy vehicle built to the design would not comply with Maximum of Difference (C8b) under the Standards and Vehicle Assessment Rules, it would not pose any greater risk than a heavy vehicle that did comply with the standard for the following reasons:</p> <ul style="list-style-type: none">• It exceeds the requirements of Low-Speed Swept Path (C7) in a way that offsets the failure to comply with Maximum of Difference (C8b). (Standard: 8.7m; This vehicle: 8.2m)• Because of its 500mm margin for Low Speed Swept Path (C7), it will operate comfortably within Level 2, despite its non-compliance with C8b and will require less road space than other vehicles that comply with Level 2 standards.• The vehicle could be made to fully comply by installing a bulbar; however, Low-Speed Swept Path (C7) and Frontal Swing (C8a) would then be on the level 2 limit. The benefits higher performance in C7 and C8a would be lost by fixing the minor nonconformance with Maximum of Difference (C8b).